

Electronic room thermostat with touch LED display

HY607LIC



Heating control



Cooling control



Ventilation control



Temperature regulation



Attractive design



Control via Wi-Fi application



Easy controls




Operating modes

- 24 V DC power supply
- control signal for the EC fan 0–10 V DC
- weekly program with three time blocks 5+2, 6+1, 7
- operating modes: manual, automatic (weekly program)
- possibility of automatic switching – heating, cooling, ventilation
- automatic or manual fan speed control in 3 steps
- control via a Wi-Fi application using an Android or iOS smartphone
- temperature setting range 5–50 °C
- operating environment -10 to 60 °C
- accuracy 0,5 °C
- dimensions w × h × d: 86 × 86 × 16 mm

Order code (white): REG-HY60724W

Order code (black): REG-HY60724B



40 €

Function description of the thermostat

The control voltage is 24 V. The HY607LIC thermostat control the heating medium valve with a thermoelectric actuator, and in addition control fan speed with a control voltage of 0–10 V DC. Fan speed may be controlled automatically by the thermostat, or manually in three speed settings.

Recommended installation

The HY607LIC thermostat is designed for semi-recessed wall mounting. For easier cable connection, we recommend using an electrical installation box with dimensions of 68 × 70 mm (e.g., KRP 68-70_KA).

Suitable for

Floor convectors with fans

KORAFLEX Optimal-V FVO
KORAFLEX Energy FVE
KORAFLEX Pool-V FVP
KORAFLEX Variant F2V
KORAFLEX Variant F4V
KORAFLEX Amper FVA

Wall convectors with fans

KORAWALL Optimal-V WVO
KORAWALL Pool-V WVP
KORAWALL Rek WVR

Floor-mounted convectors with fans

KORALINE Optimal-V LVO



If you require more detailed technical information or specifications, please do not hesitate to contact us.